dAGE316U40SAS-EXP

3U 16-bay SAS Expander RAID Storage JBOD Rackmount Chassis 750W PSU

Specifications

Dimension (W x H x D)	19 x 5.25 x 22.5 inches
Cooling	Four 80mm Cooling Fans
HDD Interface	SAS/SATA II (3Gbps)
Host Interface	One miniSAS (SFF8088)
Hot-Swap	Both on Host and Device
Material	Heavy-duty Cold-rolled Steel
Power Supply	750W Single PSU (Server grade) (with 500W redundant power supply model: dAge316U40SAS-Exp-R)
O.S. Support	OS Independent, Compatible with Windows, Linux & Mac

Features

- Supports Up to Sixteen SAS/SATA (3Gbps) Hard Drives
- Built-in SAS Expander for Single miniSAS Cable Connectivity
- LCD Control Panel for System Setup
- Backplane Design for Up to 16 Removable SAS/SATA Drive Trays
- LED Indicators for Power and Activity on Each HDD Tray
- Environmental Monitoring with Power/FAN LEDs
- Supports Two miniSAS Connectors for Next Storage Expansion
- 4 x 80mm Cooling Fans for Ventilation
- Optional Redundant Power Supply

dAGE408U20T5-2MS

4U 8-bay SATA miniSAS SFF8088 JBOD Trayless Chassis 500W PSU

Specifications

Dimension (W x H x D)	19 x 7 x 20 inches
Cooling	1 x 120mm Cooling Fan
HDD Interface	SATA I/II
Host Interface	2 miniSAS (SFF8088) Connectors
LED Display	LED for Power On/Off, HDD
Hot-Swap	Both on Host and Device
Material	Chassis: 1.2 mm SECC Zinc-Coated Steel
Power Supply	500W single psu (with 400W redundant psu model: dAge408U20T5-2MS-R)

Recommended Accesories

Model No.	Description
cAGE-AAMMM1	External mini SAS to External mini SAS Cable
cAGE-AAMSM1	External Multilane to External mini SAS Cable
zAGE-H-8788-DU	Dual Mini SAS x4 Host Adapter

Features

- Supports SATA I/II (1.5/3 Gbps)
- 2 x miniSAS (SFF8088) Interface for Easy Connection
- 120mm x 1 Cooling Fan for Ventilation
- Trayless Design
- LED Indicators for Power and Activity on Each HDD Tray
- Up to 8 Hot-Swappable 3.5" Drive Trays



727 Phillips Drive, City of Industry, CA 91748 | TEL:1-888-989-1189 | FAX: 1-626-301-0588 | www.istarusa.com